

Hybrid Inverter 75-125kW

M2HT-75/80/99/100/125K-300

48A	100%	300A
Max. PV Current per MPPT	Unbalanced Output	Max. Charge/Discharge

Commercial | Three Phase | HV Battery | 6 MPPTs



High Power & Performance

- 200% PV oversizing for higher yield
- 300A charge/discharge for high-capacity battery
- 165KVA backup peak for 10 seconds
- 24A PV input current per string

Advanced Energy Management

- AI EMS with PV forecasting
- Dynamic pricing & ToU optimization
- Accurate export control compliance
- Six preset operating modes



System Integration & Flexibility

- Dual independent battery ports
- On-grid / off-grid / parallel support
- Support diesel generator connection
- 100% unbalanced & half-wave loads

Industrial Reliability & Protection

- IP66 & C4 outdoor durability
- 330A high-current contactor
- <20 ms seamless transfer
- Auto-reverse fan dust removal

Integ M Series

The Power Master

©2026 Solinteg Power Co., Ltd. All rights reserved.
sales@solinteg.com
www.solinteg.com

Hybrid Inverter 75-125kW

Models		M2HT-75K-300	M2HT-80K-300	M2HT-99K-300	M2HT-100K-300	M2HT-125K-300
PV Side						
Max. PV Array Power	[kWp]	150	160	200	200	250
Max. PV Input Voltage *	[V]	1000				
Rated PV Input Voltage	[V]	620				
Start-up Voltage	[V]	135				
MPPT Operating Voltage Range *	[V]	160-950				
No. of MPP Trackers		6	6	6	6	6
No. of Strings per MPPT		3	3	3	3	3
Max. Input Current per MPPT	[A]	48*6	48*6	48*6	48*6	48*6
Max. Short-circuit Current per MPPT	[A]	60*6	60*6	60*6	60*6	60*6
Battery Side						
Battery Type		Lithium Battery (with BMS)				
Battery Voltage Range	[V]	300-950				
No. of Battery Input		1 or 2				
Max. Charge/Discharge Current	[A]	300 or 150*2				
Max. Charge/Discharge Power	[kW]	75/75	80/80	100/100	100/100	125/125
Grid Side (On-Grid)						
Rated Output Power	[kW]	75.0	80.0	99.0	100.0	125.0
Max. Output Apparent Power	[kVA]	75.0	80.0	99.0	100.0	125.0
Rated AC Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated AC Frequency	[Hz]	50/60				
Rated Output Current	[A]	113.9/108.7/104.2	121.2/115.9/111.1	150/143.5/137.5	151.5/144.9/138.9	189.4/181.2/173.6
Max. Output Current	[A]	113.6	121.2	150.0	151.5	189.4
Power Factor		0.8 leading ...0.8 lagging				
THDi (@Rated Power)		<3%				
Max. Input Apparent Power **	[kVA]	207				
Rated AC Voltage		3L/N/PE; 220/380V;230/400V;240/415V				
Rated AC Frequency	[Hz]	50/60				
Max. AC Input Current	[A]	300				
Back-up Side (Off-Grid)						
Rated Output Power	[kW]	75.0	80.0	99.0	100.0	125.0
Peak Output Apparent Power	[kVA]	165 @10S	165 @10S	165 @10S	165 @10S	165 @10S
Rated Output Voltage	[V]	3L/N/PE; 220/380V; 230/400V; 240/415V				
Rated Output Frequency	[Hz]	50/60				
Rated Output Current	[A]	113.6/108.7/104.2	121.2/115.9/111.1	150/143.5/137.5	151.5/144.9/138.9	189.4/181.2/173.6
On/Off-grid Switching Time		< 20ms				
THDv (@Linear Load)		<3%				
Efficiency						
MPPT Efficiency		99.90%				
Max. Efficiency		98.00%				
European Efficiency		97.80%				
Protection						
Integrated Protection		DC reverse polarity protection / Battery input reverse connection protection /Insulation resistance protection / Surge protection(DC: Type I+II, AC: Type II) /Over-temperature protection /Residual current protection / Islanding protection/AC over-voltage protection /Overload protection/AC short-circuit protection				
General Data						
Dimensions	[W×H×D mm]	1232×932×356				
Weight	[KG]	164				
Ingress Protection		IP66				
Anti-corrosion Degree		C4				
Standby Self-consumption	[W]	< 35				
Topology		Transfomerless				
Operating Temperature Range	[° C]	-30~60				
Relative Humidity	[%]	0~100				
Max. Operation Altitude	[m]	3000				
Over Voltage Category		II(PV+Battery), III(Mains+Backup)				
Cooling		Smart Fan				
Display		LED & OLED				
Communication		CAN, RS485				

* The maximum PV input voltage is 950V. The inverter will stop operating when the voltage is between 950V and 1000V. The inverter will be damaged if the voltage exceeds 1000V;
** Max input apparent power means the maximum power imported from the grid used to satisfy the backup loads and charge the battery;

©2026 Solinteg Power Co., Ltd. All rights reserved.
sales@solinteg.com
www.solinteg.com