

### MANUFACTURER:

Daqin New Energy Tech (Taizhou) Co., Ltd.

Material Safety Data Sheet

File No: 2022-12-22



Section 1 - Product and Com	pany Identification				
Product Name	LFP Lithium Ion Battery				
Battery Type	HV9640				
Battery Capacity	40Ah				
Battery Voltage	96V				
Manufacturer	Daqin New Energy Tech(Taizhou)Co., Ltd.				
Address	199 Keji Road ,Sanshui Street ,Jiangyan District ,Taizhou City,Jiangsu Province,P.R.China				
Post Code	225500				
TEL	+86-523-88510062				
Emergency Telephone	+86-523-88510062				
Section 2 - Hazard Identification					
Hazard label (CN)	GB6944 9th Goods				
NFPA Rating (USA)	0 0				



Other Hazard		of exposu mechanical electrolyt	These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or electrically abused. Contact of electrolyte and extruded lithium with skin and eyes should be avoided.			
Section 3	- Compos	sition/Information	n on ingredients			
Hazardous c	components	CAS#	% (by weight)			
LiFeP	04	15365-14-7	125-35			
Carb	oon	7440-44-0	12-22			
Electrolyte	LiPF6	21324-40-3	18-25			
Electiolyte	Solvent	/	10 20			
PF	)	9003-07-0	2-6			
Сорр	oer	7440-50-8	10-18			
Alumi	num	7429-90-5	10-20			
Section 4	- First	Aid Measures				
Skin contact		Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes, Seek medical attention immediately				
Eye contact		Immediately flush eyes with plenty of water continuously for least 15 minutes, occasionally lifting the upper and low eyelids. Seek medical attention immediately.				
Inhalation		Cover the victim in a blanket, move to the place of fresh a and keep quiet. Seek medical attention immediately. When dyspr (breathing difficulty) or asphyxia (breath-bald), gi artificial respiration immediately.				



Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.				
Section 5 - Fire Fighting Measures					
Suitable Extinguisher	Dry power, sand, carbon dioxide (CO2).				
Unsuitable Extinguisher	Water, water spray.				
Specific hazards	Risk of receptacle bursting.				
Special protective equipment for firefighters	In the event of a fire, wear full protective clothing and self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.				
NFPA	Health: 0 Flammability: 1 Instability: 0				
Section 6 - Accidental Release Measures					
Personal precautions	Remove personnel from area until dissipate. Use personal protective equipment. Avoid contact with skin and eyes.				
Environmental precautions	Prevent further leakage or spillage if safe to do so.  Do not allow material to contaminate ground water system.  Do not throw out into the environment.				



Methods for cleaning up	Dilute the leaked electrolyte with water and neutralize with diluted sulfuric acid. The leaked solid is moved to a container. The leaked place is fully flushed with water.
Section 7 - Handling and St	orage
Handling	Technical measures: Prevention of user exposure; not necessary under normal use. Prevention of fire and explosion: Not necessary under normal use. Precaution for safe handling: Do not damage or remove the external shell. Specific safe handling advice: Never throw out battery in a fire or expose to high temperatures (above 60°C). Do not soak battery in water and seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or throw down. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. In the case of charging, use only dedicated charge or charge according to the conditions specified by the supplier.



Storage	Storage conditions (suitable to be avoided) Avoid direct sunlight, high temperature, and high humidity. Store in cool place (temperature:-10~45°C, humidity: 45~85%). Incompatible products: Conductive materials, water, seawater, strong oxidizers and strong acids. Packing material: Insulative and tear-proof, waterproof materials are recommended.
Section 8 - Exposure Contro	ols and Person Protection  Use local exhaust ventilation or other
Engineering controls  Exposure limits	engineering controls to control sources of dust, mist, fume and vapor  Airborne exposures to hazardous substances are not expected when product is used for its intended
Eye protection	Not necessary under normal conditions. Wear safety glasses if handling an open or leaking cell.
Skin protection	Not necessary under normal conditions. Wear neoprene or nature rubber gloves if handling an open or leaking cell.
Hygiene Measures	Do not eat, drink or smoke in work areas.
Section 9 - Physical and Ch	



PH	N/A
Flash point(℃)	N/A
Melting point ( $^{\circ}$ )	N/A
Boiling point ( $^{\circ}$ C)	N/A
Relative density (water=1)	N/A
Relative Vapour density (air=1)	N/A
Vapour pressure (KPa)	N/A
Heat of combustion (KJ/mol)	N/A
Auto-ignition temperature ( $^{\circ}$ C)	N/A
Solubility	Insoluble in water
Lower explosive limits % (V/V)	N/A
<u></u>	
Upper explosive limits % (V/V)	N/A
Upper explosive limits % (V/V)  Section 10 - Stability and	
Section 10 - Stability and	Reactivity  Product is stable under storage conditions
Section 10 - Stability and Stability	Reactivity  Product is stable under storage conditions described in Section 7.
Section 10 - Stability and Stability Incompatibilities	Reactivity  Product is stable under storage conditions described in Section 7.  Strong oxidizing agents, acids.  Direct sunlight, high temperature and high humidity.  Do not heat above 60°C , incinerate, or expose
Section 10 - Stability and Stability Incompatibilities Conditions to avoid	Product is stable under storage conditions described in Section 7.  Strong oxidizing agents, acids.  Direct sunlight, high temperature and high humidity.  Do not heat above 60°C, incinerate, or expose contents to water.

#### 7 / 10



None unless internal materials are exposed.

Toxic information is available on the ingredients noted in section 3, but generally not available to intact batteries as used by customers.

In case of internal gas released or electrolyte spilled, electrolyte and organic solvents has small toxicity and may cause irritation of skin or eyes. Released gas may also cause irritation of skin of eyes.

### Section 12 - Ecological Information

Ecological toxicity	No data available.
Environmental	Since a battery cell and the internal materials remain in the environment, it can't be degradable. Do not throw out into the environment.
Bioaccumulation	No information.

### Section 13 - Disposal Considerations

Disposal measures

Do not throw out a used battery cell. Lithium ion cells and batteries can be disposable in accordance with appropriate federal, state and local regulations. However, we recommend recycling, since these cells and batteries contain recyclable material (LiFePO4).

### Section 14 - Transportation

UN Number	UN3480
-----------	--------



PROPER SHIPPING NAME	Lithium ion batteries(including lithium ion polymer batteries)
Packaging Group	II
sea contamination	None
Land transport (ADR/RID)	Class 9
Sea transport (IMDG)	Class 9
Air transport (ICAO-TI/IATA DGR)	Class 9
National regulations	National regulations for transport land GB12268 This battery type is classified as dangerous goods for transport, because the watt-hour rating of the battery exceeds 100 Wh. We also declare that this battery type meets the requirements of each test in the UN Manual of tests and Criteria Part III, Subsection 38.3 (ST/SG/AC.10/11/Rev.5)

### Section 15 - Regulatory Information

Major applicable regulations for the transportation of lithium—ion cells and batteries are as

follows:

The UN Model Regulations, United Nations ST/SG/AC.10/1/Rev 16. Recommendations on the Safe Transport of Dangerous Goods

The International Civil Aviation Organization (ICAO) Technical Instructions for the Safe Transport of Dangerous Goods by Air Transport

The International Air Transport Association (IATA) Dangerous Goods Regulations (57th Edition 2016)

International Maritime Organization (IMO) International Maritime Dangerous Goods Code (IMDG Code) .  $01-01\ 2014$ 

OSHA Hazard communication standard (29 CFR 1910)

USHA	Hazai u	Communicatio	n Sta	muaru	(29	CPK	1910	J)				
	Hazaro	dous	√	_Non-h	ıazar	rd						
			•			•		•	•	•		•



#### Section 16 - Other Information

The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.

This safety data sheet provider guidance on health. Safety and environmental specs of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Company	Daqin New Energy Tech(Taizhou)Co., Ltd.			
Address/Tel	199 Keji Road ,Sanshui Street ,Jiangyan District ,Taizhou City,Jiangsu Province,P.R.China			
Approved by	Zhang weizhong			
Date issued	2022-12-22			

The material safety data sheet is furnished to every manufacturer as a reference to secure the safe handling of chemical.

Every manufacturer is requested to carry out appropriate actions for chemical handling as their own responsibility. The supplier makes no warrantee, either express or implied. Concerning of this products, User assumes all risks resulting from its use.