	Ref. Certif. No.
	JPTUV-194458

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	AC Charger
Name and address of the applicant	GoodWe Technologies Co., Ltd. No.90 Zijin Rd., New District 215011 Suzhou, P.R. China
Name and address of the manufacturer	GoodWe Technologies Co., Ltd. No.90 Zijin Rd., New District 215011 Suzhou, P.R. China
Name and address of the factory Note: *When more than one factory, please report on page 2*	GoodWe (GuangDe) Power Supply Technology Co., Ltd. No. 208, Tong Rui East Road Guangde Anhui, P.R. China
Ratings and principal characteristics	Refer to page 2
Trademark / Brand (if any)	GoodWe (Logo)
Customer's Testing Facility (CTF) Stage used	N/A
Model / Type Ref.	GW7K-HCA-G30 , GW11K-HCA-G30 , GW22K-HCA-G30
Additional information (if necessary may also be reported on page 2)	See additional page(s) for further Additional information.
A sample of the product was tested and found to be in conformity with	IEC 61851-1:2017
As shown in the Test Report Ref. No. which forms part of this Certificate	CN26FHWJ 001

This CB Test Certificate is issued by the National Certification Body

TÜVRheinland®

TÜV Rheinland Japan Ltd.
4-25-2 Kita-Yamata, Tsuzuki-ku
Yokohama 224-0021, Japan
Mail: info@jpn.tuv.com

Date: 2026-10-27

Signature: A. Chen

10/061SMD 2024-12 rke-simplified

Disclaimer: This is an electronically released document. The authenticity can be verified on the IECEE Website "http://certificates.iecee.org" (1.3s / 21)

Additional information :

For model GW7K-HCA-G30:
Input: 230V a.c.,1P+N+PE,50/60Hz,32 A a.c.
Output: 230V a.c.,1P+N+PE,50/60Hz,32 A a.c.,7kW
Operating temperature: -30°C to 50°C
Protection level: IP65 Case C
IP54 Case B

For model GW11K-HCA-G30:
Input: 400V a.c.,3P+N+PE,50/60Hz,16 A a.c.
Output: 400V a.c.,3P+N+PE,50/60Hz,16 A a.c.,11kW
Operating temperature: -30°C to 50°C
Protection level: IP65 Case C
IP54 Case B

For model GW22K-HCA-G30:
Input: 400V a.c.,3P+N+PE,50/60Hz,32 A a.c.
Output: 400V a.c.,3P+N+PE,50/60Hz,32 A a.c.,22kW
Operating temperature: -30°C to 50°C
Protection level: IP65 Case C
IP54 Case B

TÜVRheinland®

Date: 2026-10-27 Signature: as on page 1

Disclaimer: This is an electronically released document. The authenticity can be verified on the IECEE Website "http://certificates.iecee.org" (p2/1.10)