



# AI LINK

For H3 Pro, R series parallel installation



## IP65 RATED

High level of protection, suitable for outdoor installation.



## WIDE OPERATING TEMPERATURE RANGE

Wide operating temperature range, suitable for a variety of environments.



## SAFE AND RELIABLE

Safe, reliable and highly compatible.



# TECHNICAL SPECIFICATIONS

<b>MODEL</b>	<b>A-1000</b>
<b>COMMUNICATION</b>	
	30
	4, modbus RTU, sunspec, 9600bps, 19200bps, 38400bps, 57600bps, 115200bps
	2, RJ45, 10M/100M
	6 ~ 24
	3, Relay
	LTE-FDD: B1, B3, B7, B8, B20, B28A
	LTE-TDD: B38,B40,B41
	WCDMA: B1,B8
	802.11 b / g / n / ac
	HT20 / 40 MHz
	2.4GHz
<b>INDICATOR LIGHTS</b>	
LED	3 LEDs
Button	Start
<b>POWER</b>	
DC Input Voltage [Vdc]	10 ~ 27
Consumption [W]	Standard 20, Max<30
<b>ENVIRONMENTAL CONDITION</b>	
Working Temperature [°C]	-30 ~ +60
Storage Temperature [°C]	-40 ~ +70
Relative Humidity [%]	≤95 ( No Condensation )
Altitude [m]	≤4000
Ingress Protection	IP65
<b>GENERAL PROPERTY</b>	
Dimension (W*H*D) [mm]	260*192*88
Weight [kg]	2.5
Installation Method	Wall mount, indoor, outdoor