



## DESIGN REPORT OF SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025



<b>Name of the sample</b>	Rechargeable Li-ion Battery System E2BR-S64K-C		
<b>Applicant</b>	Wuxi Solinteg Power Co., Ltd.		
<b>Supplier</b>	Suzhou DeBo New Energy Co., Ltd.		
<b>Composition of the sample</b>	LiFePO4: 37%; LiPF6: 3.2%; Aluminum: 6.4%; Graphite: 19.1%; Copper: 10.5%; Polyethylene: 5.5%; Ethyl methyl carbonate: 12.2%; Ethylene carbonate: 6.1%		
<b>Warranty of Design</b>	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) Tenth revised edition		
Design Result of MSDS please see next page.			
<b>Designer</b>	孙越越	<b>Approver</b>	For and on behalf of CCIC JIANGSU CO., LTD. 中国检验认证集团江苏有限公司 华安

4

授权签字人 Authorized Signature (s)

Notes: This MSDS is valid before the implementation of the Eleventh revised edition GHS.

Test is Located on: CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)  
Tel: +86-519-83277160

Rechargeable Li-ion Battery  
System E2BR-S64K-C

Warranty of Design: GHS (Tenth Revised  
Edition)

# SAFETY DATA SHEET

MSDS

No.: 250100320452593E

Date: Jul.8 2025

Version:



## Section 1 Product and Company Identification

### > Product Identifier

**Product Name** Rechargeable Li-ion Battery System E2BR-S64K-C

**Synonyms** -

### > Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

**Relevant Identified Uses** Please consult manufacturer.

**Uses Advised Against** Please consult manufacturer.

### > Details of the Supplier of the Safety Data Sheet

**Applicant Name** Wuxi Solinteg Power Co., Ltd.

**Application Address** Building H1-1001, No. 6 Jingxian Road, Xinwu District, 214135 Wuxi, Jiangsu, P.R. China

**Applicant Post Code** 214135

**Applicant Telephone** +86-510-68222510

**Applicant Fax** —

**Applicant E-mail** service@solinteg.com

**Supplier Name** Suzhou DeBo New Energy Co., Ltd.

**Supplier Address** Building 6, Comprehensive Bonded Zone No.688 Pangjin Road Wujiang District Suzhou, Jiangsu, P.R. China

**Supplier Post Code** 215200

**Supplier Telephone** +86-512-63036928

**Supplier Fax** —

**Supplier E-mail** east.wang@163.com

### > Emergency Phone Number

**Emergency Phone Number** +86-510-68222510

## Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the tenth revised edition):

### > GHS Hazard Class

This product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev.10 (2023) Part 1.3.2.1.1]

### > GHS Label Elements

Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

MSDS

Version: 1.1

**Pictogram** Not applicable

**Signal Word** **Not applicable**

## > Hazard Statements

Not applicable

## > Precautionary Statements

### Prevention

Do not open or disassemble.  
Do not expose to high temperatures or open fire.  
Do not mix with batteries of varying sizes, chemistries or types.  
Avoid using external impact battery.

### Response

Not applicable

### Storage

Store under roof in cool, dry, well-ventilated areas.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 3 Composition/Information on Ingredients

Component	CAS No.	EC No.	Concentration (weight percent, %)
LiFePO4	15365-14-7	-	37
LiPF6	21324-40-3	244-334-7	3.2
Aluminum	7429-90-5	231-072-3	6.4
Graphite	7782-42-5	231-955-3	19.1
Copper	7440-50-8	231-159-6	10.5
Polyethylene	9002-88-4	-	5.5
Ethyl methyl carbonate	623-53-0	-	12.2
Ethylene carbonate	96-49-1	202-510-0	6.1

## Section 4 First Aid Measures

### > Description of First Aid Measures

#### General Advice

Immediate medical attention is required. Show this safety data sheet (MSDS) to the doctor in attendance.

#### Eye Contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

MSDS

Version: 1.1

## Skin Contact

Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

## Ingestion

Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

## Inhalation

Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.

## Protecting of First-aiders

Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

## > Most Important Symptoms and Effects, both Acute and Delayed

- 1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

## > Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

## Section 5 Fire Fighting Measures

### > Extinguishing Media

#### Suitable Extinguishing Media

Use water spray to extinguish fire. Cool surrounding Lithium batteries with water spray.

#### Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter or spread fire.

### > Specific Hazards Arising from the Substance or Mixture

- 1 Containers may explode when heated.
- 2 Fire exposed containers may vent contents through pressure relief valves.
- 3 May expansion or decompose explosively when heated or involved in fire.

### > Advice for Firefighters

- 1 As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.


## Section 6 Accidental Release Measure

### > Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Ensure adequate ventilation. Remove all sources of ignition.
- 2 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 3 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

### > Environmental Precautions

- 1 Prevent further leakage or spillage if safe to do so.



Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

MSDS

Version: 1.1

- 2 Discharge into the environment must be avoided.

## > Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## Section 7 Handling and Storage

### > Precautions for Handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.
- 5 Take precautionary measures against static discharges.

### > Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

## Section 8 Exposure Controls/Personal Protection

### > Control Parameters

#### Occupational Exposure Limit Values

Component	Country/Region	Limit Value - Eight Hours		Limit Value - Short Term	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Aluminum 7429-90-5	USA - OSHA	-	15	-	-
	South Korea	-	10	-	-
	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-
Graphite 7782-42-5	USA - OSHA	-	15	-	-
	South Korea	-	2	-	-
	Ireland	-	10	-	-
	Germany (DFG)	-	4	-	-

Rechargeable Li-ion Battery System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

## MSDS

Version: 1.1

Copper 7440-50-8	Denmark	-	2.5	-	5
	Australia	-	3 (4)	-	-
	The Netherlands	-	0.1	-	-
	Poland	-	0.2	-	-
	Latvia	-	0.5	-	1
	Germany (DFG)	-	0.01	-	0.02

### Biological Limit Values

Component	Source	Biological monitoring index	Biological limits value	Sampling time	Remark
LIPF6	SCOEL(EU)	Fluorine/urine	8mg/L	end of shift	

### Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160 Determination of toxic substances in workplace air(Series effective standard)and GBZ/T 300 Determination of toxic substances in workplace air(Series standard).

### > Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

### > Personal Protection Equipment

- Eye Protection** Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
- Hand Protection** Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU),US F739 or AS/NZS 2161.1 standard.
- Respiratory protection** If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
- Skin and Body Protection** Wear fire/flare resistant/retardant clothing and antistatic boots.

## Section 9 Physical and Chemical Properties

**Appearance:** Rechargeable Li-ion Battery System (型号 E2BR-S64K-C, 204.8V 314Ah 64.3kWh) is assembled from 4 battery modules (E2BR-B16K, 51.2V 314Ah 16.08kWh), individually packaged

**Odor Threshold:** No information available

**Melting Point/Freezing Point (°C):** No information available

**Flash Point (°C)( Closed Cup):** Not applicable

**Flammability:** No information available

**Vapor Pressure (KPa):** Not applicable

**Odor:** No information available

**pH:** No information available

**Initial Boiling Point and Boiling Range (°C):** No information available

**Evaporation Rate:** Not applicable

**Upper/lower explosive limits%(v/v):** Upper limit: No information available; Lower limit: No information available

**Relative Vapour Density(Air=1):** Not applicable



Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

MSDS

Version: 1.1

**Relative Density(Water=1):** No information available  
**n-Octanol/Water Partition Coefficient:** No information available  
**Decomposition Temperature (°C):** No information available  
**Particle characteristics:** No information available

**Solubility:** No information available  
**Auto-Ignition Temperature(°C):** No information available  
**Kinematic Viscosity (mm<sup>2</sup>/s):** Not applicable  
**Critical Temperature(°C):** Not applicable

## Section 10 Stability and Reactivity

<b>Reactivity</b>	Contact with incompatible substances can cause decomposition or other chemical reactions.
<b>Chemical Stability</b>	Stable under proper operation and storage conditions.
<b>Possibility of Hazardous Reactions</b>	Ultrafine powder will self-ignite in the air at room temperature. Mixtures with metallic acetylene, when heated, cause a fire or incandescence. Reacts severely with halogens, interhalogens or other strong oxidants, or causes a fire.
<b>Conditions to Avoid</b>	Incompatible materials, heat, flame and spark.
<b>Incompatible Materials</b>	Oxidants, halogen, interhalogen and mercury. Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid. Halogen, interhalogen, strong oxidant, water and acids.
<b>Hazardous Decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11 Toxicological Information

### > Acute Toxicity

Component	CAS No.	LD <sub>50</sub> (Oral)	LD <sub>50</sub> (Dermal)	LC <sub>50</sub> (Inhalation, 4h)
LiPF <sub>6</sub>	21324-40-3	50~300mg/kg(Rat)	275mg/kg(Rat)	No information available
Ethylene carbonate	96-49-1	10000mg/kg(Rat)	> 3000mg/kg(Rabbit)	No information available

### > Skin Corrosion/Irritation

No information available

### > Serious Eye Damage/Irritation

No information available

### > Skin Sensitization

No information available

### > Respiratory Sensitization

Rechargeable Li-ion Battery  
System E2BR-S64K-C  
Warranty of Design: GHS (Tenth Revised Edition)

# SAFETY DATA SHEET

No.: 250100320452593E  
Date: Jul.8,2025  
Version: 1.1

## MSDS

No information available

### > Germ Cell Mutagenicity

No information available

### > Carcinogenicity

ID	CAS No.	Component	IARC	NTP
1	15365-14-7	LiFePO4	Not Listed	Not Listed
2	21324-40-3	LiPF6	Not Listed	Not Listed
3	7429-90-5	Aluminum	Not Listed	Not Listed
4	7782-42-5	Graphite	Not Listed	Not Listed
5	7440-50-8	Copper	Not Listed	Not Listed
6	9002-88-4	Polyethylene	Category 3	Not Listed
7	623-53-0	Ethyl methyl carbonate	Not Listed	Not Listed
8	96-49-1	Ethylene carbonate	Not Listed	Not Listed

### > Reproductive Toxicity

No information available

### > Reproductive Toxicity (Additional)

No information available

### > STOT-Single Exposure

No information available

### > STOT-Repeated Exposure

No information available

### > Aspiration Hazard

No information available

## Section 12 Ecological Information

### > Acute Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Aluminum	7429-90-5	LC <sub>50</sub> : 1.55mg/L (96h)(Fish)	No information available	No information available
Copper	7440-50-8	LC <sub>50</sub> : 0.665mg/L (96h)(Fish)	EC <sub>50</sub> : 0.02mg/L (48h)	ErC <sub>50</sub> : 7.9mg/L (96h)



Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

**MSDS**

Version: 1.1

## > Chronic Aquatic Toxicity

No information available

## > Others

**Persistence and Degradability** No information available

**Bioaccumulative Potential** No information available

**Mobility in Soil** No information available

### Results of PBT and vPvB Assessment

LiFePO4 does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

LiPF6 does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Aluminum does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Graphite does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Copper does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Polyethylene does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Ethyl methyl carbonate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Ethylene carbonate does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

## Section 13 Disposal Considerations

### Waste Chemicals Contaminated Packaging Disposal Recommendations

Before disposal should refer to the relevant national and local laws and regulation. Containers may still present chemical hazard when empty. Keep away from heat and ignition source of fire. Return to supplier for recycling if possible. Refer to Waste chemicals and Contaminated packaging.

## Section 14 Transport Information

### Transporting Label



**Marine pollutant** No

**UN Number** 3480

**UN Proper Shipping Name** LITHIUM ION BATTERIES(including lithium ion polymer batteries)

**Transport Hazard Class** 9

**Transport Subsidiary Hazard Class** NONE

**Packing Group** Packagings shall conform to the packing group II performance level



Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised Edition)

MSDS

Version: 1.1

**Report remarks**

According to United Nations Recommendations on the Transports of Dangerous Goods•Model Regulations, Lithium batteries(group) could be transported in accordance with the classification conclusions of this report when meet the requirements of UN38.3 test.

## Section 15 Regulatory Information

### > International Chemical Inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECL	AIIC	ENCS
LiFePO4	×	√	√	√	×	×	√	×	×
LiPF6	√	√	×	√	×	√	√	√	×
Aluminum	√	√	√	√	√	√	√	√	×
Graphite	√	√	√	√	√	√	√	√	×
Copper	√	√	√	√	√	√	√	√	×
Polyethylene	×	√	√	√	√	√	√	√	√
Ethyl methyl carbonate	√	√	×	√	×	√	√	×	√
Ethylene carbonate	√	√	√	√	√	√	√	√	√

- [EINECS] European Inventory of Existing Commercial Chemical Substances.
- [TSCA] United States Toxic Substances Control Act Inventory.
- [DSL] Canadian Domestic Substances List.
- [IECSC] China Inventory of Existing Chemical Substances.
- [NZIoC] New Zealand Inventory of Chemicals.
- [PICCS] Philippines Inventory of Chemicals and Chemical Substances.
- [KECL] Korea Existing Chemicals List.
- [AIIC] Australian Inventory of Industrial Chemicals.
- [ENCS] Japan List of Existing and New Chemical Substances.

**Note**

“√” Indicates that the substance included in the regulations

“×” That no data or included in the regulations

## Section 16 Additional Information

**Creation Date** Jul.8,2025  
**Revision Date** Jul.8,2025  
**Reason for Revision** -

### > Disclaimer

This Safety Data Sheet (MSDS) was prepared according to UN GHS (the 10th revised edition).The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of

Rechargeable Li-ion Battery  
System E2BR-S64K-C

# SAFETY DATA SHEET

No.: 250100320452593E

Date: Jul.8,2025

Warranty of Design: GHS (Tenth Revised  
Edition)

**MSDS**

Version: 1.1

information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.





## Terms of the Using of the Report

1. The report is issued by CCIC according to the information of the chemicals and the information of its shipping provided by the applicant (shipper or his agent).
2. According to the demand of this MSDS, CCIC requires the applicant to provide true and exact sample and data.
3. Information from applicant is the key of this MSDS, so CCIC will not respond for the wrong of applicant.
4. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
5. This report will be effective only after it is signed by the inspector, approver and stamped by CCIC.
6. CCIC guarantees the objectivity and fairness of this report, and carries out confidentiality obligations on business secrets such as business information, technical documents and so on.
7. The partly duplicating of this report is prohibited without the written approver of CCIC.
8. The report is invalid when anything of the following happens-illegal transfer, embezzlement, imposture, modification or tampering in any media form.
9. The authenticity of the certificate can be checked by scan the security code of this certificate.



**Notes : Test is Located on : CCIC Dangerous Goods Identification Center (47 Qingyang North Road, Tianning District, Changzhou, China)**

**Tel : +86-519-83277160**